

SERIE
NITOR WL



SERIE NITOR WL

		Dry content (%)	Light fastness*	SOLUBILITY	
				Water	Polar solvents
White WL - PT		39 +/-3	8	good	good
Lemon Yellow WL - M		34 +/-3	6-7	good	good
Yellow WL - G		28 +/-3	6-7	good	good
Red WL - 2B		24 +/-3	6	good	good
Blue WL - R		30 +/-3	8	good	good
Green WL - G		32 +/-3	8	good	good
Black WL - K		31 +/-3	8	good	good

* 1-8 Blue wool scale

Serie Nitor WL

Nitor WL dyes are selected transparent pigment organic-aqueous dispersions dedicated to wood and leather application. They are absolutely miscible among each other.

They are dilutable with water and polar solvents, and they are suitable for tinting of wood (frames, decorations and furniture components, both with rollers and with manual airbrushes and automatic sprayer machines) and leather finishing.

Spray System

If You use **Nitor WL** in a spray tinting system, we suggest a dilution form 1:5 to 1:20 with water (depending on depth of shade). In order to reduce time of drying an addition of 10-30% of acetone or alcohol is suggested.

If deeper wetting of pores is needed, add 10-20% of glycols (PM or DPM).

Roller System

For the usage of **Nitor WL** within a roller tinting system, no or low dilution is needed (1:1, 1:2 with water in case of pale shade). For better pores wetting add 10-20% of glycols (PM or DPM).

Preparation of wood

Suggested sand paper is around 150-180.

Drying times

Spray system: 2-3 hours at room temperature.

Roller system: 30 - 60" with IR radiations or hot air (40° - 50°C).

Other data

Expiry date: 9 months at room temperature.

Packaging: 25 kg plastic tanks. Other packaging available on request.

All information are based on the current state of our knowledge and on the results of our tests, but they are given without guarantee. The Buyer remains responsible for verifying that the products are suitable for his intended process or purpose. Tests before the industrial use of the product are recommended.



COLORANTI, PIGMENTI E PRODOTTI CHIMICI PER L'INDUSTRIA
INDUSTRIAL DYES, PIGMENTS AND CHEMICAL PRODUCTS

Cromatos s.r.l.

Via G. Cardano, 6B/C/D | 47122 Forlì (FC) Italy | T +39 0543 796191 | F +39 0543 796189
info@cromatos.com | www.cromatos.com