

SERIE

PATINA SL



PATINA SERIE SL

PATINA SERIE SL		Dry content (%)	Light fastness ★	SOLUBILITY			
				Acetone	Ethanol	Nitro diluents	Poliurethanic diluents
White T-SL		18 +/- 2	8	good	good	good	good
Yellow G-SL		18 +/- 2	7	good	good	good	good
Red S-SL		18 +/- 2	7/8	good	good	good	good
Olive Green G-SL		18 +/- 2	8	good	good	good	good
Dark Brown T-SL		17 +/- 2	6	good	good	good	good
Black SX-SL		18 +/- 2	8	good	good	good	good

★ 1- 8 Blue wool scale on full shade.

Patina are “ready to use” pigment suspensions dedicated to wood application, in particular to obtain aged effect and rustic effect on finished furniture.

Patina are dilutable in solvents like acetone and alcohol but can also be apply directly.

Application must be done by spray or roll with an excess of product followed by redistribution and removal with hand made artistic effect by cloth or soft sponge while still wet.

Aeer drying patina effect is suggest to be fixed with a over lack solvent or water based as desired.

Application must be done on flat, framed panels or also on finish furniture.

Preparation on wood is suggested by sanding with sand paper 150-180

Other data

Product must be well stirred before usage.

Expiry time 9 months at room temperature in sealed container.

All information are based on the current state of our knowledge and on the results of our tests, but they are given without guarantee. The Buyer remains responsible for verifying that the products are suitable for his intended process or purpose.

Tests before the industrial use of the product are recommended.

Edition: may 2019



COLORANTI, PIGMENTI E PRODOTTI CHIMICI PER L'INDUSTRIA
INDUSTRIAL DYES, PIGMENTS AND CHEMICAL PRODUCTS

Cromatos s.r.l.

Via G. Cardano, 6B/C/D | 47122 Forlì (FC) Italy | T +39 0543 796191 | F +39 0543 796189
info@cromatos.com | www.cromatos.com